



## AUTO PLUS 20W-40 SL/CF

**PERFORMANCE LEVELS: Meets and Exceeds**

Cummins CES 20074 & ISUZU CNG Engines, Detroit Diesel DDC-93K216

Danzol **Auto Plus** CNG Engine oil Formulated with 100% virgin base stock and multiple additives using latest technology CNG or LNG engines. Auto Plus CNG engine oil provides superior lubrication for both on- and off-road engines for commercial, personal or off-road application or as recommended by OEM.

Suitable for all requiring API SL with 20W-40 viscosity grade or as recommended by the OEM.

### Typical properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE			<b>20W-40</b>
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D1500	2.5
DENSITY @20°C	G/ML	ASTM D4052	0.8840
KINEMATIC VISCOSITY @100°C	cSt	ASTM D 445	14.50
KINEMATIC VISCOSITY @40°C	cSt	ASTM D 445	Report
VISCOSITY INDEX	NA	ASTM D2270	127
CORRECTED FLASH POINT	°C	ASTM D92	232
HOMOGENEITY/MISCIBILITY	NA	ASTM D6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D97	-24
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D2896	9.2

### Advantages:

Compatible with Exhaust-Gas Recirculation (EGR)  
Advance technology has both mineral and synthetic base stock  
Environment friendly  
Exhibits easier cold weather starting  
Resists breakdown at high temperatures.  
Withstands the stress of heat, wear and corrosion  
Longer drain intervals and smooth running of engines.  
Longer drain intervals and smooth running of engines.

### Application:

- Use in ferrous and non-ferrous mills.
- Back-up roll bearing system.
- High speed rolling mills.