



AUTO PLUS 20W-50 SL/CF

PERFORMANCE LEVELS: Meets and Exceeds

Cummins CES 20074 & ISUZU CNG Engines, Detroit Diesel DDC-93K216

Danzol **Auto Plus** CNG Engine oil Formulated with 100% virgin base stock and multiple additives using latest technology CNG or LNG engines. Auto Plus CNG engine oil provides superior lubrication for both on- and off-road engines for commercial, personal or off-road application or as recommended by OEM.

Suitable for all requiring API SL with 20W-50 viscosity grade or as recommended by the OEM.

Typical properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE			20W-50
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D1500	2.5
DENSITY @20°C	G/ML	ASTM D4052	0.8840
KINEMATIC VISCOSITY @100°C	cSt	ASTM D 445	17.50
KINEMATIC VISCOSITY @40°C	cSt	ASTM D 445	Report
VISCOSITY INDEX	NA	ASTM D2270	125
CORRECTED FLASH POINT	°C	ASTM D92	246
HOMOGENEITY/MISCIBILITY	NA	ASTM D6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D97	-24
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D2896	9.2

Advantages:

- Compatible with Exhaust-Gas Recirculation (EGR)
- Advance technology has both mineral and synthetic base stock
- Environment friendly
- Exhibits easier cold weather starting
- Resists breakdown at high temperatures.
- Withstands the stress of heat, wear and corrosion
- Longer drain intervals and smooth running of engines.
- Longer drain intervals and smooth running of engines.

Application:

- Use in ferrous and non-ferrous mills.
- Back-up roll bearing system.
- High speed rolling mills.