



LORYPLUS 10000 SAE 15W-50 CI-4/SL

PERFORMANCE LEVELS: Meets and Exceeds

ACEA E5/E7, MB 229.1, CAT ECF-1a ECF-2/3, ALLISON C-4, MAN 3275, MIL-L-2104D, CUMMINS CES 20081, VOLVO VDS-3, RENAULT RLD-3

Danzol **LORYPLUS 10000** Heavy-Duty Diesel Engine oil (HDDEO) formulated with the multiple advance additive's technology. LORYPLUS 10000 diesel engine oil provides superior lubrication for both on- and off-road diesel engines with EGR or DPF and high speed four stroke diesel engines for commercial, personal or off-road application or as recommended by OEM.

Typical properties:

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE		ASTM	15W-50
APPEARANCE	NA	VISUAL	B&C
COLOR	NA	ASTM D-1500	3.0
DENSITY @29.5°C	g/mL	ASTM D-4052	0.8800
KINEMATIC VISCOSITY @100°C	cSt	ASTM D-445	18.5
KINEMATIC VISCOSITY @40°C	cSt	ASTM D-445	Report
VISCOSITY INDEX	NA	ASTM D-2270	136
CORRECTED FLASH POINT	°C	ASTM D-92	230
HOMOGENEITY/MISCIBILITY	NA	ASTM D-6922	Pass
ACCEPTABLE ODOR	NA	VISUAL	Agreeable
POUR POINT	°C	ASTM D-97	-30
TOTAL BASE NO. (TBN)	mg KOH/g	ASTM D-2896	10.5

Advantages:

- Exhibits easier cold weather starting
- Resists breakdown at high temperatures.
- Resisting deposits caused by soot and acids
- Withstands the stress of heat, wear and corrosion
- Longer drain intervals and smooth running of engines.
- Good compatibility with rubber to Protect rubber seals.
- Increases fuel economy due to ultra-low vaporization loss.
- Specially designed for Engine with EGR and turbochargers fitted.
- Highly efficient in dispersancy and detergency keeps engine clean.
- Reduces Kinetic energy loss out of friction wear by effectively dispersing ash and deposits.

Performance Specification:

- This product meets or exceeds the following specifications
- API CI-4 and lower API, such as CH-4 and CF-4

Applications:

- Use for all diesel engines where API CI-4 or lower and above service grade recommended by the manufacturer. Serves best for diesel engines with EGR system and turbochargers.