



MAGIC 4T 10W-40 SM

PERFORMANCE LEVELS: Meets and Exceeds

API-SM, JASO (T903): MA2, ILSAC, GF-3, ACEA, A1/B1, A3/B3, A3/B4

Danzol **Magic 4T Engine Oil** is for low, medium and high cylinder capacity 4-stroke engines. Magic 4T oil is semi synthetic and blended with high quality performance base stock and advance technology additive system. Magic 4T oil is suitable for driving long distances without worrying about performance loss or premature wear in different situation.

Typical properties:

| PROPERTY | UNIT | TEST METHOD | TYPICAL VALUES |
|----------------------------|----------|-------------|----------------|
| SAE VISCOSITY GRADE | | ASTM | 10W40 |
| APPEARANCE | NA | VISUAL | B&C |
| COLOR | NA | ASTM D-1500 | 2.5 |
| DENSITY @29.5°C | g/mL | ASTM D-4052 | 0.8700 |
| KINEMATIC VISCOSITY @100°C | cSt | ASTM D-445 | 14.50 |
| KINEMATIC VISCOSITY @40°C | cSt | ASTM D-445 | 104 |
| VISCOSITY INDEX | NA | ASTM D-2270 | 145 |
| CORRECTED FLASH POINT | °C | ASTM D-92 | 238 |
| HOMOGENEITY/MISCIBILITY | NA | ASTM D-6922 | Pass |
| ACCEPTABLE ODOR | NA | VISUAL | Agreeable |
| POUR POINT | °C | ASTM D-97 | -36 |
| TOTAL BASE NO. (TBN) | mg KOH/g | ASTM D-2896 | 9.5 |

Applications:

- Air and liquid cooled four stroke motorcycle engines
- Motor Bike with or without immersed clutches.
- Motor Bike with back torque limiters.
- Motor bike with exhaust catalytic converters.

Advantages:

- Provides good friction on clutch disc, preventing slippage and premature wear in joint engine and transmission (wet clutch) lubrication system.
- Environment friendly.
- Exhibits easier cold weather starting.
- Resists breakdown at high temperatures.
- Withstands the stress of heat, wear and corrosion
- Longer drain intervals and smooth running of engines.
- Good compatibility with rubber to Protect rubber seals.
- Increases fuel economy due to ultra-low vaporization loss.
- Highly efficient in dispersancy and detergency keeps engine clean.
- Specialized additives help prevent ring sticking and buildup of harmful deposit.

Performance Specification:

- This product meets or exceeds the following specifications
- API SM
- JASO (T903): JASO MA-2