

Technical data sheet

# **SYMERO 10000 SAE 5W-30 SN-(GF-5)**

## **PERFORMANCE LEVELS: Meets and Exceeds**

ACEA C3, BMW LL-04, PORSCH A40, MB 229.31/229.51, VW 502.00/505.00, DEXOS-2, RENAULT RN 0700/0710

Danzol **SYMERO 10000** Fully synthetic motor oil. our most advanced formulation fortified with most effective additives and blended using latest technology for most demanding modern high-performance engines.

Suitable for all gasoline, diesel, gas or duel fuel engines of passenger cars, light duty commercial vehicles, and off-road SUV's requiring API SN with 5W-30 viscosity grade or as recommended by the OEM. It helps lower the maintenance cost by keeping your engine clean providing reduced engine wear and improving performance.

#### **Typical properties:**

| PROPERTY                   | UNIT     | TEST METHOD | TYPICAL VALUES |
|----------------------------|----------|-------------|----------------|
| SAE VISCOSITY GRADE        |          | ASTM        | 5W-30          |
| APPEARANCE                 | NA       | VISUAL      | B&C            |
| COLOR                      | NA       | ASTM D-1500 | 2.5            |
| DENSITY @29.5°C            | g/mL     | ASTM D-4052 | 0.8250         |
| KINEMATIC VISCOSITY @100°C | cSt      | ASTM D-445  | 10.20          |
| KINEMATIC VISCOSITY @40°C  | cSt      | ASTM D-445  | Report         |
| VISCOSITY INDEX            | NA       | ASTM D-2270 | 165            |
| CORRECTED FLASH POINT      | °C       | ASTM D-92   | 228            |
| HOMOGENEITY/MISCIBILITY    | NA       | ASTM D-6922 | Pass           |
| ACCEPTABLE ODOR            | NA       | VISUAL      | Agreeable      |
| POUR POINT                 | °C       | ASTM D-97   | -42            |
| TOTAL BASE NO. (TBN)       | mg KOH/g | ASTM D-2896 | 9.50           |

#### Advantages:

- Fully Synthetic formulation.
- Environment friendly.
- Keeps your engine like factory clean.
- Superior wear and corrosion protection.
- Excellent fuel economy and energy efficiency.
- Longer drain intervals and smooth running of engines.
- Helps quick cold weather starting.

### **Applications:**

- For modern gasoline, diesel, gas and duel fuel engines or as recommended by the OEM.
- Serves best for high-end German, Japanese, Korean cars and buses wherever a lubricant of this grade recommended by the OEM.
- Suitable for all engines requiring API SN Oils such as SN, series and 5W-30 viscosity.