



SYPA CLP 150

PERFORMANCE LEVELS: Meets and Exceeds

DIN 51517 Part III, AGMA 9005 E-02, DAVID BROWN, S1.53 101(E)

Danzol SYPA Industrial Gear Oil 150 is a good quality synthetic oil, formulated with PAO base stocks and antifoam additive package. Suitable for the lubrication of Hydraulic systems, pumps enclosed industrial gears and bearings operating under mild conditions. Also, used for industrial applications where oil losses are high and heavy contaminants require frequent oil change.

Typical properties:

CHARACTERISTICS	TEST METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE		150
DENSITY @ 15°C, KG/L	ASTM D-1298	0.8610
VISCOSITY @ 40°C, cSt	ASTM D-445	150.50
VISCOSITY @ 100°C, cSt	ASTM D-445	22.25
VISCOSITY INDEX	ASTM D-2270	175
FLASH POINT, COC, °C	ASTM D-92	236
TAN mg/KOH	ASTM D-664	0.95
POUR POINT, °C	ASTM D-97	-45

Advantages:

- Excellent resistance to degradation at high temperature.
- Fair resistance to rust and corrosion
- Good demulsibility power
- Excellent protection against foaming
- Low traction
- Effective rust and corrosion protection